

CERTIFICATE

No. U6 001119 0025 Rev. 01

Holder of Certificate: **ZHUHAI LITECH TECHNOLOGY CO., LTD.**

15th Building, No.3, Pingdong 6th Road
Nanping Technical Industrial Park
519060 Zhuhai, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:




Product: **Power supplies
(LED DRIVER)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142205019502

Date, 2023-05-09



(Taylor Yao)

CERTIFICATE

No. U6 001119 0025 Rev. 01

Model(s): SE-15-350-700-G1T; SE-15-150-500-G1T;
SE-12-100-400-G1T; SE-12-350-700-G1T;
SE-9-350-700-G1T; SE-9-550-900-G1T

Brand Name: LTSYS, LTECH

LTSYS® LTECH

Parameters:

Rated Input Voltage: 220-240VAC
Rated Frequency: 50/60Hz
Rated Input Current: See below table for details
Rated Output: See below table for details
Protection against Electric Shock: Class II; SELV
Degree of Protection: IP20
Method of Installation: Independent
Type of Output: Constant current type
ta: -20~45°C
tc: 90°C

Tested according to: EN 61347-2-13:2014/A1:2017
EN 61347-1:2015/A1:2021
EN IEC 62384:2020

Production Facility(ies): 001119

CERTIFICATE

No. U6 001119 0025 Rev. 01

Model No.	Rated Input Current (A) Max.	Output Voltage (VDC)	I _{rated} (mA)	DIP Switch Position			U _{out} (VDC)	P _{rated} (W) Max.
				1	2	3		
SE-15-350-700-G1T	0.1	9-42	350	OFF	OFF	OFF	50	15
		9-37.5	400	OFF	OFF	ON		
		9-33	450	OFF	ON	OFF		
		9-30	500	OFF	ON	ON		
		9-27	550	ON	OFF	OFF		
		9-25	600	ON	OFF	ON		
		9-23	650	ON	ON	OFF		
		9-21.5	700	ON	ON	ON		
SE-15-150-500-G1T	0.1	9-42	150	OFF	OFF	OFF	50	15
		9-42	200	OFF	OFF	ON		
		9-42	250	OFF	ON	OFF		
		9-42	300	OFF	ON	ON		
		9-42	350	ON	OFF	OFF		
		9-37.5	400	ON	OFF	ON		
		9-33	450	ON	ON	OFF		
		9-30	500	ON	ON	ON		
SE-12-100-400-G1T	0.09	9-42	100	OFF	OFF	ON	50	12
		9-42	150	OFF	ON	OFF		
		9-42	200	OFF	ON	ON		
		9-42	250	ON	OFF	OFF		
		9-40	300	ON	OFF	ON		
		9-34	350	ON	ON	OFF		
		9-30	400	ON	ON	ON		
SE-12-350-700-G1T	0.09	9-24	350	OFF	OFF	OFF	30	12
		9-24	400	OFF	OFF	ON		
		9-24	450	OFF	ON	OFF		
		9-24	500	OFF	ON	ON		
		9-21.5	550	ON	OFF	OFF		
		9-20	600	ON	OFF	ON		
		9-18.5	650	ON	ON	OFF		
		9-17	700	ON	ON	ON		
SE-9-350-700-G1T	0.08	2-12	350	OFF	OFF	OFF	22	8.4
		2-12	400	OFF	OFF	ON		
		2-12	450	OFF	ON	OFF		
		2-12	500	OFF	ON	ON		
		2-12	550	ON	OFF	OFF		
		2-12	600	ON	OFF	ON		
		2-12	650	ON	ON	OFF		
		2-12	700	ON	ON	ON		
SE-9-550-900-G1T	0.08	2-10	550	OFF	OFF	OFF	22	9
		2-10	600	OFF	OFF	ON		
		2-10	650	OFF	ON	OFF		
		2-10	700	OFF	ON	ON		
		2-10	750	ON	OFF	OFF		
		2-10	800	ON	OFF	ON		
		2-10	850	ON	ON	OFF		
		2-10	900	ON	ON	ON		