



Proof of RCM Compliance

Cert.No.: POC23072012

Date of issue: 12-Jul-2023

Certificate Holder:

ZHUHAI LTECH TECHNOLOGY CO., LTD.

Address:

15th Building, No.3, Pingdong 6th Road, Nanping Technical Industrial Park, 519060 Zhuhai, Guangdong, PEOPLE'S REPUBLIC OF CHINA

Product Description:

LED Driver

Brand/Trade Name:

LTECH & LTSYS

Model Number:

SE-15-350-700-G1T
SE-15-150-500-G1T
SE-12-100-400-G1T
SE-12-350-700-G1T
SE-9-350-700-G1T
SE-9-550-900-G1T

Electrical Ratings:

Input:Refer to model list

Output:Refer to model list

AusRCM Compliance certifies that the Electrical/Electronic Article(s) as described above meets the requirements of the standard(s) listed below;

Compliance for:

Evidenced by:

ACMA mandated
standards –eg.EMC

Test report and Declaration of Conformity
EN IEC 55015:2019/A11:2020;EN IEC 61000-3-2:2019/A1:2021;
EN 61000-3-3:2013/A2:2021;EN 61547:2009

Electrical Safety
Standard(s):

Certificate of Approval and/or Certificate of Conformity
AS 61347.2.13: 2018;AS/NZS 61347.1: 2016 Inc A1;
SAA-230731-EA
Date of Expire: 12-Jul-2028

EESS- National
Equipment Database
registration

Checked above model number(s) being registered as
LEVEL 3 product on
<https://equipment.era.gov.au/Registration/EquipmentSearch.aspx?atn=public>

As of above, the Applicable Compliance mark shall be:





On behalf of AusRCM Compliance

Suite 206, 585 Little Collins Street, Melbourne ,VIC, 3000, Australia.



Proof of RCM Compliance

Cert.No.: POC23072012

Appendix -Model list

Model	Rating
SE-15-350-700-G1T	Input: 220-240VAC, Max.0.1A, 50/60Hz, Class II, IP20, independent, ta/tc:-20~45°C/90°C Output:9-42Vdc, 350-700mA, Max 50Vdc, Max 15W, IC
SE-15-150-500-G1T	Input: 220-240VAC, Max.0.1A, 50/60Hz, Class II, IP20, independent, ta/tc:-20~45°C/90°C Output:9-42Vdc, 150-500mA, Max 50Vdc, Max 15W, IC
SE-12-100-400-G1T	Input: 220-240VAC, Max.0.09A, 50/60Hz, Class II, IP20, independent, ta/tc:-20~45°C/90°C Output:9-42Vdc, 100-400mA, Max 50Vdc, Max 12W, IC
SE-12-350-700-G1T	Input: 220-240VAC, Max.0.09A, 50/60Hz, Class II, IP20, independent, ta/tc:-20~45°C/90°C Output:9-24Vdc, 350-700mA, Max 30Vdc, Max 12W, IC
SE-9-350-700-G1T	Input: 220-240VAC, Max.0.08A, 50/60Hz, Class II, IP20, independent, ta/tc:-20~45°C/90°C Output:2-12Vdc, 350-700mA, Max 22Vdc, Max 8.4W, IC
SE-9-550-900-G1T	Input: 220-240VAC, Max.0.08A, 50/60Hz, Class II, IP20, independent, ta/tc:-20~45°C/90°C Output:2-10Vdc, 550-900mA, Max 22Vdc, Max 9W, IC