



Proof of RCM Compliance

Cert.No.: POC23084016

Date of issue: 22-Aug-2023

Updated on: 30-Aug-2023

Certificate Holder: ZHUHAI LTECH TECHNOLOGY CO., LTD.
Address: 15th Building, No.3, Pingdong 6th Road, Nanping Technical Industrial Park, 519060 Zhuhai, Guangdong, PEOPLE'S REPUBLIC OF CHINA
Product Description: LED DRIVER
Brand/Trade Name: LTECH
Model Number: SE-40-300-1050-W2D
Refer to model list
Electrical Ratings: Input:Refer to model list
Output:Refer to model list

AusRCM Compliance certifies that the Electrical/Electronic Article(s) as described above meets the requirements of the standard(s) listed below;

Compliance for: **Evidenced by:**

ACMA mandated standards –eg.EMC

Test report and Declaration of Conformity

ETSI EN 301 489-1 V2.2.3(2019-11);ETSI EN 301 489-3 V2.3.2 (2023-01);EN IEC 55015:2019/A11:2020;EN 61547:2009;EN IEC 61000-3-2:2019/A1:2021; EN 61000-3-3:2013/A2:2021;ETSI EN 300 330 V2.1.1 (2017-02); EN 62479:2010; EN 50663:2017;

Electrical Safety Standard(s):

Certificate of Conformity

AS 61347.2.13: 2018;AS/NZS 61347.1: 2016+A1

GMA-516185-EA

Date of Expire: 11-Aug-2028

EESS- National Equipment Database registration

Checked above model number(s) being registered as LEVEL 3 product on

<https://equipment.erac.gov.au/Registration/EquipmentSearch.aspx?atn=public>

As of above, the Applicable Compliance mark shall be:




On behalf of AusRCM Compliance

Suite 206, 585 Little Collins Street, Melbourne ,VIC, 3000, Australia.



Proof of RCM Compliance

Cert.No.: POC23084016

Appendix -Model list

Model	Rating
SE-40-300-1050-W2D	Input: 100-240V AC, 50/60Hz, 0.47A Max, 120-250V DC, 0.15-0.4A Output: 9-42Vdc, 0.3-1.05A, 40W Max.
SE-40-300-1050-W1D	Input: 100-240V AC, 50/60Hz, 0.47A Max, 120-250V DC, 0.15-0.4A Output: 9-42Vdc, 0.3-1.05A, 40W Max.
SE-30-200-800-W2D	Input: 100-240V AC, 50/60Hz, 0.37A Max, 120-250V DC, 0.11-0.3A Output: 9-42Vdc, 0.2-0.8A, 30W Max.
SE-30-200-800-W1D	Input: 100-240V AC, 50/60Hz, 0.37A Max, 120-250V DC, 0.11-0.3A Output: 9-42Vdc, 0.2-0.8A, 30W Max.
SE-40-300-1050-W2B	Input: 100-240V AC, 50/60Hz, 0.47A Max, 120-250V DC, 0.15-0.4A Output: 9-42Vdc, 0.3-1.05A, 40W Max.
SE-40-300-1050-W1B	Input: 100-240V AC, 50/60Hz, 0.47A Max, 120-250V DC, 0.15-0.4A Output: 9-42Vdc, 0.3-1.05A, 40W Max.
SE-30-200-800-W2B	Input: 100-240V AC, 50/60Hz, 0.37A Max, 120-250V DC, 0.11-0.3A Output: 9-42Vdc, 0.2-0.8A, 30W Max.
SE-30-200-800-W1B	Input: 100-240V AC, 50/60Hz, 0.37A Max, 120-250V DC, 0.11-0.3A Output: 9-42Vdc, 0.2-0.8A, 30W Max.
SE-40-300-1050-W2A	Input: 100-240V AC, 50/60Hz, 0.47A Max, 120-250V DC, 0.15-0.4A Output: 9-42Vdc, 0.3-1.05A, 40W Max.
SE-40-300-1050-W1A	Input: 100-240V AC, 50/60Hz, 0.47A Max, 120-250V DC, 0.15-0.4A Output: 9-42Vdc, 0.3-1.05A, 40W Max.
SE-30-200-800-W2A	Input: 100-240V AC, 50/60Hz, 0.37A Max, 120-250V DC, 0.11-0.3A Output: 9-42Vdc, 0.2-0.8A, 30W Max.



Proof of RCM Compliance

Cert.No.: POC23084016

Appendix -Model list

Model	Rating
SE-30-200-800-W1A	Input: 100-240V AC, 50/60Hz, 0.37A Max, 120-250V DC, 0.11-0.3A Output: 9-42Vdc, 0.2-0.8A, 30W Max.
SE-40-300-1050-W2M	Input: 100-240V AC, 50/60Hz, 0.47A Max, 120-250V DC, 0.15-0.4A Output: 9-42Vdc, 0.3-1.05A, 40W Max.
SE-40-300-1050-W1M	Input: 100-240V AC, 50/60Hz, 0.47A Max, 120-250V DC, 0.15-0.4A Output: 9-42Vdc, 0.3-1.05A, 40W Max.
SE-30-200-800-W2M	Input: 100-240V AC, 50/60Hz, 0.37A Max, 120-250V DC, 0.11-0.3A Output: 9-42Vdc, 0.2-0.8A, 30W Max.
SE-30-200-800-W1M	Input: 100-240V AC, 50/60Hz, 0.37A Max, 120-250V DC, 0.11-0.3A Output: 9-42Vdc, 0.2-0.8A, 30W Max.