



Product Service

CERTIFICATE

No. B 001119 0027 Rev. 01

Holder of Certificate: **ZHUHAI LITECH TECHNOLOGY CO., LTD.**

15th Building, No.3, Pingdong 6th Road
Nanping Technical Industrial Park
519060 Zhuhai, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product:

**Power supplies
(LED DRIVER)**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 651402013202

Valid until: 2028-04-27

Date, 2023-04-28

(Taylor Yao)

CERTIFICATE

No. B 001119 0027 Rev. 01

Model(s): SE-15-350-700-G1T; SE-15-150-500-G1T;
SE-12-100-400-G1T; SE-12-350-700-G1T;
SE-9-350-700-G1T; SE-9-550-900-G1T

Brand Name: LTSYS, LTECH

LTSYS® LTECH

Parameters:

Rated Input Voltage: 220-240VAC

Rated Frequency: 50/60Hz

Rated Input Current: See below table for details

Rated Output: See below table for details

Protection against Electric Shock: Class II; SELV

Degree of Protection: IP20

Method of Installation: Independent

Type of Output: Constant current type

ta: -20~45°C

tc: 90°C

Tested according to: EN 61347-2-13:2014/A1:2017
EN 61347-1:2015/A1:2021
EN 62493:2015/A1:2022
BS EN 61347-2-13:2014/A1:2017
BS EN 61347-1:2015/A1:2021
BS EN 62493:2015/A1:2022

CERTIFICATE

No. B 001119 0027 Rev. 01

Model No.	Rated Input Current (A) Max.	Output Voltage (VDC)	I _{rated} (mA)	DIP Switch Position			U _{out} (VDC)	P _{rated} (W) Max.
				1	2	3		
SE-15-350-700-G1T	0.1	9-42	350	OFF	OFF	OFF	50	15
		9-37.5	400	OFF	OFF	ON		
		9-33	450	OFF	ON	OFF		
		9-30	500	OFF	ON	ON		
		9-27	550	ON	OFF	OFF		
		9-25	600	ON	OFF	ON		
		9-23	650	ON	ON	OFF		
SE-15-150-500-G1T	0.1	9-21.5	700	ON	ON	ON	50	15
		9-42	150	OFF	OFF	OFF		
		9-42	200	OFF	OFF	ON		
		9-42	250	OFF	ON	OFF		
		9-42	300	OFF	ON	ON		
		9-42	350	ON	OFF	OFF		
		9-37.5	400	ON	OFF	ON		
SE-12-100-400-G1T	0.09	9-33	450	ON	ON	OFF	50	12
		9-30	500	ON	ON	ON		
		9-42	100	OFF	OFF	ON		
		9-42	150	OFF	ON	OFF		
		9-42	200	OFF	ON	ON		
		9-42	250	ON	OFF	OFF		
		9-40	300	ON	OFF	ON		
SE-12-350-700-G1T	0.09	9-34	350	ON	ON	OFF	30	12
		9-30	400	ON	ON	ON		
		9-24	350	OFF	OFF	OFF		
		9-24	400	OFF	OFF	ON		
		9-24	450	OFF	ON	OFF		
		9-24	500	OFF	ON	ON		
		9-21.5	550	ON	OFF	OFF		
SE-9-350-700-G1T	0.08	9-20	600	ON	OFF	ON	22	8.4
		9-18.5	650	ON	ON	OFF		
		9-17	700	ON	ON	ON		
		2-12	350	OFF	OFF	OFF		
		2-12	400	OFF	OFF	ON		
		2-12	450	OFF	ON	OFF		
		2-12	500	OFF	ON	ON		
SE-9-550-900-G1T	0.08	2-12	550	ON	OFF	OFF	22	9
		2-12	600	ON	OFF	ON		
		2-12	650	ON	ON	OFF		
		2-12	700	ON	ON	ON		
		2-10	550	OFF	OFF	OFF		
		2-10	600	OFF	OFF	ON		
		2-10	650	OFF	ON	OFF		
SE-9-550-900-G1T	0.08	2-10	700	OFF	ON	ON	22	9
		2-10	750	ON	OFF	OFF		
		2-10	800	ON	OFF	ON		
		2-10	850	ON	ON	OFF		
		2-10	900	ON	ON	ON		