



China

Attestation of Conformity

No. T8AUK 001119 0067 Rev. 00

Holder of Attestation: **ZHUHAI LTECH TECHNOLOGY CO., LTD.**

15th Building, No.3, Pingdong 6th Road
Nanping Technical Industrial Park
519060 Zhuhai, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Product: **Power supplies
(LED DRIVER)**

This Attestation of Conformity is issued on a voluntary basis in support of Schedule 2 Module A Conformity Assessment of the Radio Equipment Regulations 2017. On the basis of the referenced test reports, the samples of the listed product were found to comply with the essential requirements of the above mentioned regulation as implemented in the standards used valid at the time the tests were carried out. For the requirements of the Regulation 6(2) of the Radio Equipment Regulations 2017 only UK Designated Standards valid at the moment of issuing were used. The used standards cover the essential requirements of the Radio Equipment Regulations 2017 as applicable to this product. The manufacturer must ensure compliance of the manufactured products with the technical documentation and other requirements of the Radio Equipment Regulations 2017 that apply to them. National legal requirements have to be considered before bringing the product to the market. For details see: www.tuvsud.com/ps-cert

Test report no.: 659402300401

Date, 2023-07-26

(Laurent Yuan)

Page 1 of 3

This Attestation does not replace the regulatory UK Declaration of Conformity (DoC) and does not allow for UKCA marking. After preparation of the necessary technical documentation and establishing compliance to requirements of all applicable regulations, the manufacturer may sign a DoC and apply the UKCA marking. The DoC is issued under the sole responsibility of the manufacturer.



China

Attestation of Conformity

No. T8AUK 001119 0067 Rev. 00

Model(s): SE-40-300-1050-W2D; SE-40-300-1050-W1D;
SE-30-200-800-W2D; SE-30-200-800-W1D;
SE-40-300-1050-W2A; SE-40-300-1050-W1A;
SE-30-200-800-W2A; SE-30-200-800-W1A;
SE-40-300-1050-W2M; SE-40-300-1050-W1M;
SE-30-200-800-W2M; SE-30-200-800-W1M

Parameters:

Rated Input Voltage: 120-250VDC and 100-240VAC

Rated Frequency: 50/60Hz for [100-240VAC]

Rated Input Current: See below table for details

Rated Output: See below table for details

Protection Class: II

Test Report No.:

659402300401 [EN 300 330, EN 62479, EN 50663];

657402302701 [EN 301 489-1, EN 301 489-3, EN IEC 55015,

EN 61547, EN IEC 61000-3-2, EN 61000-3-3];

211-900534-000 [EN 61347-2-13, EN 61347-1, EN 62493]

Tested according to:

EN 300 330 V2.1.1:2017

EN 62479:2010

EN 50663:2017

EN 301 489-1 V2.2.3:2019

EN 301 489-3 V2.3.2:2023

EN IEC 55015:2019/A11:2020

EN 61547:2009

EN IEC 61000-3-2:2019/A1:2021

EN 61000-3-3:2013/A2:2021

EN 61347-2-13:2014/A1:2017

EN 61347-1:2015/A1:2021

EN 62493:2015/A1:2022

Page 2 of 3

This Attestation does not replace the regulatory UK Declaration of Conformity (DoC) and does not allow for UKCA marking. After preparation of the necessary technical documentation and establishing compliance to requirements of all applicable regulations, the manufacturer may sign a DoC and apply the UKCA marking. The DoC is issued under the sole responsibility of the manufacturer.



China

Attestation of Conformity

No. T8AUK 001119 0067 Rev. 00

Model	Rated Input Voltage	Rated Input Current (A)	Output Voltage (VDC)	I _{rated} (A)	U _{out} (VDC)	P _{rated} (W) Max.
SE-40-300-1050-W2D	120-250VDC	0.15-0.4	9-42	0.3-1.05	55	40
	100-240VAC	0.47 Max.				
SE-40-300-1050-W1D	120-250VDC	0.15-0.4	9-42	0.3-1.05		40
	100-240VAC	0.47 Max.				
SE-30-200-800-W2D	120-250VDC	0.11-0.3	9-42	0.2-0.8		30
	100-240VAC	0.37 Max.				
SE-30-200-800-W1D	120-250VDC	0.11-0.3	9-42	0.2-0.8		30
	100-240VAC	0.37 Max.				
SE-40-300-1050-W2A	120-250VDC	0.15-0.4	9-42	0.3-1.05		40
	100-240VAC	0.47 Max.				
SE-40-300-1050-W1A	120-250VDC	0.15-0.4	9-42	0.3-1.05		40
	100-240VAC	0.47 Max.				
SE-30-200-800-W2A	120-250VDC	0.11-0.3	9-42	0.2-0.8		30
	100-240VAC	0.37 Max.				
SE-30-200-800-W1A	120-250VDC	0.11-0.3	9-42	0.2-0.8		30
	100-240VAC	0.37 Max.				
SE-40-300-1050-W2M	120-250VDC	0.15-0.4	9-42	0.3-1.05		40
	100-240VAC	0.47 Max.				
SE-40-300-1050-W1M	120-250VDC	0.15-0.4	9-42	0.3-1.05		40
	100-240VAC	0.47 Max.				
SE-30-200-800-W2M	120-250VDC	0.11-0.3	9-42	0.2-0.8		30
	100-240VAC	0.37 Max.				
SE-30-200-800-W1M	120-250VDC	0.11-0.3	9-42	0.2-0.8		30
	100-240VAC	0.37 Max.				

Page 3 of 3

This Attestation does not replace the regulatory UK Declaration of Conformity (DoC) and does not allow for UKCA marking. After preparation of the necessary technical documentation and establishing compliance to requirements of all applicable regulations, the manufacturer may sign a DoC and apply the UKCA marking. The DoC is issued under the sole responsibility of the manufacturer.

